



## APPENDIX

18. (Twice Amended) A self-adhering surface covering comprising:

a substrate;

a pressure-sensitive adhesive layer disposed on the substrate and having an adhesive surface distal from the substrate, the adhesive layer comprising a substantially non-stringing adhesive; and

a barrier layer disposed substantially on and covering between about 1% to about 10% of the adhesive surface, wherein the barrier layer comprises substantially non-adhesive particles [selected from the group consisting of calcium carbonate, barium carbonate, calcium sulfate, barium sulfate, aluminum sulfate, molybdenum disulfide, titanium oxide, aluminum hydroxide, alumina, silica, magnesium oxide, calcium oxide, calcium hydroxide, ferrous oxide, ferric oxide, cured rubbers, ebonite, resins, and combinations thereof, wherein the substantially non-adhesive particles] exhibiting a crush resistance of at least about 10 psi, and the substantially non-adhesive particles are non-hollow.

55. (NEW) The surface covering of claim 18, wherein the non-adhesive particles are selected from the group consisting of calcium carbonate, barium carbonate, calcium sulfate, barium sulfate, aluminum sulfate, molybdenum disulfide, titanium oxide, aluminum hydroxide, alumina, silica, magnesium oxide, calcium oxide, calcium hydroxide, ferrous oxide, ferric oxide, cured rubbers, ebonite, resins, and combinations thereof, wherein the substantially non-adhesive particles exhibit a crush resistance of at least about 10 psi.

RECEIVED  
NOV 20 2002  
TC 1700 MAIL ROOM